

Comfort Step Diamond

The mat with an ideal balance of comfort and performance.

An engineering marvel, Comfort Diamond has a durable, integrated slip-resistant wear layer of high-density vinyl foam polymetrically bonded to a resilient and supportive vinyl sponge cushion. Its smooth yet supple wear layer is easy to clean, while the expanded foam sponge reduces stress on legs and joints for added comfort and performance.



Flooring Solutions that Simplify.
1+ 877 285 8899 • www.porticosystems.com



Anti - Fatigue

Comfort Step Diamond

Comfort Step Diamond

1/2" DUAL-LAYER ANTI-FATIGUE MATTING



SUGGESTED USES (Not limited to)

Customer service areas, industrial areas, light-duty work areas, etc.

Manufacturing Process: High density vinyl foam polymerically bound to a moisture resistant a closed-cell vinyl sponge

Surface Aspect: Diamond pebble

Overall Gauge (± 10%): 0.500" ± 0.050" (1/2", 500mils)

Available Sizes: 2' x 3' | 3' x 5' | 3' x 12' | 3' x 60' | 4' x 60'
Custom Sizes at a Premium.

LIMITED WARRANTY

Full Commercial Warranty 1 year
Summary of Warranty:

Portico Systems warrants Comfort Diamond Dual-Layer Anti-Fatigue Matting against wear for a period of 1 year in a commercial application. This warranty applies only to material that is properly installed and maintained, while being used as intended and recommended. If the defect is covered by this warranty and is reported to Portico Systems within the warranty period, Portico Systems will supply new material of same or similar grade to repair or replace the defective material.

- Wear
Defined as complete removal of wear layer, pattern and color due to wear from normal traffic and maintenance. If the wear occurs within 1 year from date of purchase, Portico Systems will provide replacement materials or repair, of only the effected area.
- Manufacturing Defects
Portico Systems warrants Comfort Diamond Dual-Layer Anti-Fatigue Matting materials are free from manufacturing defects and will replace defective floor covering and reasonable installation costs for a period of up to one [1] year from date of purchase. Portico Systems will not pay labor costs to repair or replace materials that defects were apparent before or at the time of installation.
- Other Limitations
 - This warranty is non-transferable.
 - Manufacturing defect must be reported within 3 months from date of purchase.
 - This warranty covers only properly installed & maintained floors.
 - Portico Systems excluded and will not pay for any consequential or incidental expenses.
 - Portico Systems reserves the right of final judgment and may refuse claims in certain instances.

*For a copy of the full warranty please ask for a warranty sheet

Experience It For Yourself

Talk with your sales representative or request samples at samples@porticosystems.com

TECHNICAL SPECIFICATIONS

Tensile Strength (ASTM D412, Die C):	50 lbs/sq. in minimum
Elongation (ASTM D412, Die C):	75% minimum
Tear Strength (ASTM D624, Die C):	15 lbs/in minimum
Durometer (ASTM D2240):	75 ± 5 (Shore OO)

FLAMMABILITY

Horizontal Burn Test (DOT FMVSS 302):	Pass
Methenamine Tablet Test (CPSC FF 1-70)	Pass, < 1" diameter

MAINTENANCE

Comfort Diamond can be mopped or wiped clean with a damp cloth.

IMPORTANT NOTICE

Sample swatches have been cut from an overall design; decoration and shade may vary.

NOTES:

YOUR AUTHORIZED SALES REPRESENTATIVE:

