

# Natures View

Style Rustique 40 mil | 18" x 36" Luxury Vinyl Tile

*The warmth and appeal of natural stone with the resilience and easy maintenance of vinyl.*

Natures View luxury vinyl tiles are composed of three vinyl layers: a vinyl backing layer, a vinyl print film layer, and a tough vinyl top wear layer.

- The heavy gauge backing and annealed construction offer excellent dimensional stability and wear resistance
- tough vinyl top wear layer ensures superior stain resistance as well as lower maintenance
- all the advantages of vinyl and adding the look and texture of natural materials



01. Silver Knight NVC3744 02. Titanium NVC3724



**portico**  
SYSTEMS

**Solutions that Simplify.**

1+ 877 285 8899 · [www.porticosystems.com](http://www.porticosystems.com)



Luxury Vinyl Tile

18" x 36" Luxury Vinyl Tile

40  
MIL



# Natures View

## Style Rustique 40mil | 18" x 36" Luxury Vinyl Tile



### SUGGESTED USES

Beauty Salons, Conference Rooms, Corporate Lunchrooms, General Office, Hospitals, Libraries, Pharmacies, Retail/Department Stores, Resorts, Restaurants, Spas and Supermarkets

Manufacturing Standard: Class III Printed Film Vinyl Tile; 1x-Coated

Overall Thickness 3.175mm · 0.125"  
Wear Layer Thickness 1.0mm · 40mil  
Tile Size 18" x 36" | 18" x 18"

### LIMITED WARRANTY

Full Commercial Warranty 21 years  
Summary of Warranty

\*For a copy of the full warranty please ask for a warranty sheet Natures View tile must be professionally installed to validate the warranty. Portico Systems, Inc. warrants Natures View Style Rustique first quality tile against wear for a period of 21 years in a commercial application. This warranty applies only to material that is properly installed and maintained, while being used as intended and recommended. If the defect is covered by this warranty and is reported to Portico Systems, Inc. within the Warranty period, Portico Systems, Inc. will supply new material of same or similar grade to repair or replace the defective material.

- **Wear**  
Defined as complete removal of wear layer, pattern and color due to wear from normal traffic and maintenance. If the wear occurs within 21 years from date of purchase, Portico Systems, Inc. will provide replacement materials or repair, of only the effected area.
- **Manufacturing Defects**  
Portico Systems, Inc. warrants Style Rustique first quality tile materials are free from manufacturing defects and will replace defective floor covering and reasonable installation costs for a period of up to one (1) year from date of purchase. Portico Systems, Inc. will not pay labor costs to repair or replace materials that defects were apparent before or at the time of installation.
- **Other Limitations**
  - This warranty is non-transferable
  - Manufacturing defect must be reported within 3 months from date of purchase.
  - This Warranty covers only properly installed & maintained floors
  - Portico Systems, Inc. excluded and will not pay for any consequential or incidental expenses.
  - Portico Systems, Inc. reserves the right of final judgment and may refuse claims in certain instances.

### PACKING & DIMENSIONS

Tile 18" x 36": 8 tiles/carton  
Sq. Ft. per carton: 36 sq. ft  
Overall Thickness 3.175mm · 0.125"  
Wear Layer Thickness 1.0mm · 40mil  
Weight per Tile: 4.365 lbs | 36 lbs./carton

### TECHNICAL SPECS

Stability (EN 986) Pass  
Abrasion Resistance (EN 660) Excellent (<0.15g/1000 cycles)  
Static Load (ASTM F970 - Modified) 2000 psi  
Sound Insulation (DIN 52210) 4dB  
Slip Resistance (ASTM D 2047) Pass (Exceeds ADA Recommendations)  
Stain & Chemical Resistance (ASTM 925) Pass  
Light Resistance (F 1515) Pass  
Indentation Resistance (F 1914) Pass (<8%)

### FLAMMABILITY RATING

Radiant Panel Test (ASTM E648) Class 1  
Smoke Density (ASTM E662) Pass (<450 sdi)  
Heat Stability (ASTM 1514) Pass  
HUD/FHA Requirements Exceeds

### INSTALLATION

Surface Preparation: Sub floor (wood or concrete) must be structurally sound, clean, smooth, dry free from dust, dirt, wax, grease, and/or any other foreign material that would interfere with a good bond. DO NOT USE adhesives where moisture is present in concrete or wood-type sub floors. Moisture may retard or prevent adhesive from setting. Primer: Latex primer acts like a sealer but allows adhesion of the tile to the concrete floors. It also helps preventing moisture from getting between the tile and sub floor. Tools required: Utility knife, carpenter square, chalk, string, pencil and rolling pin.

### INSTALLATION GUIDE

Style Rustique tile and adhesive must be conditioned at room temperature, minimum 65°F for 24 hours before and 24 hours after installation. Porous Substrate- Spread adhesive with a 1/16" x 1/16" square trowel. Non-Porous substrate will require a 1/16" x 1/32" x 1/32" U notch trowel. Apply adhesive to subfloor according to the instructions on the container. Spread adhesives over a small area to avoid letting the adhesive dry too much before you have finished laying your plank. Planks use the wet set installation instructions. Roll each section immediately upon completing with a 100 lbs. three-section roller. Re-roll the entire floor after one or two hours. If you do not have a roller, then use a rolling pin and your body weight. Do not wash or treat the floor for a minimum of 48 hours after installation. For a complete guide go to our website or call your rep.

### MAINTENANCE

We recommend using a non-rising cleaner that leaves no film and suggest that you vacuum, sweep or dust mop twice per week. High-traffic areas might require more frequent cleaning. Wipe up food and other spills immediately using recommended cleaner and a soft cloth. You should NEVER USE ABRASIVE CLEANERS, POWDERS, OIL CLEANERS, WAXES OR DISH DETERGENT. These will scratch the surface or leave a film. When using a vacuum, if possible turn off the beater and use a hose or wand with an upholstery attachment. Vacuum wheel may also be a source for indenting and scuffing, check the wheels for embedded grit. To remove scuff marks you can use a soft cloth to rub it out. If they difficult to remove try using a product named "Oops Painter Wipes". Rinse the area well afterwards with clean warm water and allow to dry. Please note that these procedures may help remove stains from vinyl floors, but cannot guarantee complete removal. Burns, holes or "permanent" stains may require a replacement "patch of that section of the floor. To remove damaged tile you can use a hair dryer, which heats up the adhesive allowing the tile to be picked up. When the tile is up, use a wide blade putty knife and pull it out, then put the new tile down once the surface has been prepared. You should NEVER USE A HEAT GUN as this emits too much heat and will damage the tile.

### IMPORTANT NOTICE

Sample swatches have been cut from an overall design, decoration & shade may vary. The random nature of wood and other natural materials from which our patterns are designed means that significant color and design variation is normal and enhances the look of the tile.

### YOUR AUTHORIZED SALES REPRESENTATIVE:



experience it for yourself  
Talk with your sales representative or request samples at [samples@porticosystems.com](mailto:samples@porticosystems.com)

### Solutions that Simplify.

1+ 877 285 8899 · [www.porticosystems.com](http://www.porticosystems.com)

Luxury Vinyl Tile

18" x 36" Luxury Vinyl Tile