

Two-n-One Hybrid Mat

Meet our most versatile, customizable and scrape-n-clean entry system.

Two-n-One hybrid matting system: the smart and versatile combination of Frontrunner SB – a heel-and-wheel friendly grid entry system – and your choice of a durable all-weather walk-off carpet*, together in a single mat.

The distinctive look of Frontrunner SB's serrated grid scrapes and captures dirt and debris, while the walk-off carpet* wipes away what's left, including excess moisture. Made using Portico Systems' industry-leading assembly process, Two-n-One Mat is built to withstand medium to high traffic.

Choose from a wide selection of shapes, sizes and colors (single tone or custom logo designs available), or as a semi-permanent wall-to-wall installation. Two-n-One's nearly limitless versatility is one of the many ways Portico Systems makes customizing mats easier than ever.



Made with or without a logo in fully customizable sizes.

AVAILABLE CARPETS: Portico Nop, Premier Nop, Astoria Nop, and Kensington



portico Flooring Solutions that Simplify.
SYSTEMS 1+ 877 285 8899 · www.porticosystems.com



Custom Logo

Two-n-One

Two-n-One

> HYBRID ENTRY MATTING



SUGGESTED USES

Indoor entryways or other high-traffic areas with no mat well.


AVAILABLE CARPET

Portico Nop	54 oz.
Astoria Nop	37 oz.
Kensington	30 oz.

*All technical specifications listed below use Portico Nop.

SPECIFICATIONS

Overall Thickness	0.5 in.
Grid Thickness	0.375 in.
Total Carpet Height*	0.47 in.
Carpet Pile Height*	0.25 in.
Carpet Pile Weight*	54 oz./sy
Total Carpet Weight*	78 oz./sy
Carpet Backing*	Premium Composite Rubber
Grid Backing	Flexible PVC
Edging Material	PVC
Roll Width	3'3"
Roll Width	33' (standard)



EDGING OPTIONS

- Low Profile*
- ADA Compliant

LIMITED WARRANTY

2 years - Ask for warranty sheet for details

TECHNICAL SPECIFICATIONS (using Portico Nop Carpet)

Grid Material	Flexible PVC (Ribbed Grid)
Carpet Fiber*	100% Solution-dyed, UV stabilized ASOTA® polypropylene (Non-woven hobnail (berber) pattern)
Dimensional Stability (ASTM D7570-09)*	Pass
Electrostatic Propensity (EN 1815)*	>2kV
Electrical Resistivity (IBM / ICL)*	Pass, for R.H. ≥ 40%
Sound Insulation (ISO 10140-1:2010)*	≥ 21dB
Thermal Retention (ISO 11092)*	0.15 m K/W Pass

COLOR FASTNESS (using Portico Nop Carpet)

To Light (ISO 105 B02)*	5
To Water (ISO 105 B01)*	5
To Shampoo (ISO 105 B06)*	4-5
To Rubbing (ISO 105 B02)*	Dry: 4 Wet: 3-4

FLAMMABILITY

Smoke Density (ASTM E662)	Passes
Surface Flammability (FF 1-70/ASTM D2859)	Passes

ENVIRONMENT

Portico Systems does not use any substances currently included in the SVHC (Substances of Very High Concern) list under REACH (Registration, Evaluation, Authorization and Restriction of Chemical substances) in any matting products. All PVC grid products are 100% recyclable.

LEED-NC:

MR CREDIT 4 IEQ CREDITS 4.1, 4.3, 5

MAINTENANCE

DAILY: Vacuum with an industrial cleaner. Should stones, salt particles or other solid matter become embedded between the surface ribs, remove using a blunt instrument (screwdriver) or similar device. In addition to daily routine above, its important to remove chewing gum deposits and stains as they appear.
WEEKLY: Complete daily cleaning routine, then clean top surface using cylindrical brush machine. Initially work in direction of top ribs then across the ribs to complete cleaning. If a cylindrical brush machine is not available equally good results can be achieved using a high-pressure water extraction process.

For more information on Two-n-One installation or maintenance, contact your Portico Systems sales representative.

*NOTE: Other Portico Systems sheet/roll goods available as walk-off carpet, potentially changing specifications marked with an asterisk. Contact your representative for more information.

NOTES:

YOUR AUTHORIZED SALES REPRESENTATIVE:



experience it for yourself

Talk with your sales representative or request samples at samples@porticosystems.com

Custom Logo

Two-n-One